

MODEL	06EA/EX/ET	150	250	265	266	175	275	199	299
NET OIL PRESSURE		12-22	12-22	12-22	12-22	12-22	12-22	12-22	12-22
CYLINDERS		4	4	6	4	6	6	6	6
BORE		2-11/16	2-11/16	2-11/16	2-11/16	2-11/16	2-11/16	2-11/16	2-11/16
STROKE		2-3/8	2-3/8	2	2-7/8	2-3/16	2-3/16	2-7/8	2-7/8
DISPLACEMENT CFM		50.3	50.3	68.9	66.0	75.4	75.4	99.0	99.0
OIL GRADE		150	150	150	150	150	150	150	150
OIL CHARGE	PINTS	14	14	19	14	19	19	19	19
NET WEIGHT		410	425	465	420	470	480	500	530
RATED BTUH X 1000	R-22		223.3	300.3	290.0		332.8		437.9
	AIR COOLED								
	R-22	245.8	247.0	334.7	302.6	364.3	363.0	469.7	476.3
	WATER COOLED								
MOTOR SIZE	HP	15	20	25	25	25	30	35	40
ELECTRICAL DATA									
208-230 -3- 60	LRA	283.0	345.0	446.0	446.0	446.0	506.0	610.0	690.0
	RLA	72.0	87.0	112.0	112.0	112.0	135.0	155.0	189.0
	MTA	90.0	108.0	140.0	140.0	140.0	168.0	193.0	236.0
460 -3- 60	LRA	142.0	173.0	205.0	205.0	205.0	220.0	265.0	300.0
	RLA	36.0	44.0	57.0	57.0	57.0	65.0	82.0	97.0
	MTA	45.0	54.0	71.0	71.0	71.0	81.0	102.0	121.0
575 -3- 60	LRA	98.0	120.0	164.0	164.0	164.0	176.0	212.0	240.0
	RLA	31.0	36.0	46.0	46.0	46.0	52.0	65.0	77.0
	MTA	38.0	45.0	57.0	57.0	57.0	65.0	82.0	97.0

Air Cooled 45° SST, 130° SCT, 0° Subcooling Water Cooled 40° SST, 105° SCT, 0° Subcooling