

MODEL	06EM/EZ	150	266	175	199	
NET OIL PRESSURE		12-22	12-22	12-22	12-22	
CYLINDERS		4	4	6	6	
BORE		2-11/16	2-11/16	2-11/16	2-11/16	
STROKE		2-3/8	2-7/8	2-3/16	2-7/8	
DISPLACEMENT CFM		50.3	66.0	75.4	99.0	
OIL GRADE		150	150	150	150	
OIL CHARGE	PINTS	14	14	19	19	
NET WEIGHT		410	420	470	500	
RATED BTUH X 1000	R-12	15 ⁰ F	82.6		121.0	163.4
	R-22	40 ⁰ F	219.7	277.0	323.8	422.6
	R-502	-25 ⁰ F				
	R-502	20 ⁰ F	139.0	180.0	207.5	280.0
MOTOR SIZE	HP	15	25	25	35	
ELECTRICAL DATA						
208-230 -3- 60	LRA XL	283.0	446.0	446.0	610.0	
	MAX RLA	72.0	112.0	112.0	155.0	
	MTA	90.0	140.0	140.0	193.0	
460 -3- 60	LRA XL	142.0	223.0	223.0	305.0	
	MAX RLA	36.0	56.0	56.0	77.0	
	MTA	46.0	70.0	70.0	96.0	
575 -3- 60	LRA XL	98.0	164.0	164.0	212.0	
	MAX RLA	31.0	46.0	46.0	62.0	
	MTA	38.0	57.0	57.0	77.0	

NOTE: (R12, 150 SST, 1100 SCT, 650 RGT)(R22, 400 SST, 1200 SCT, 600 RGT)(R502, -250 SST, 1100 SCT, 650 RGT)(R502, 200 SST, 1200 SCT, 650 RGT)