

MODEL	06GH	040	240	060	160	260
OLD MODEL NUMBER		6G40	6G45	6G60	6G63	6G65
NET OIL PRESSURE		40-60	40-60	40-60	40-60	40-60
CYLINDERS		4	4	6	6	6
BORE		2-1/2	2-1/2	2-1/2	2-1/2	2-1/2
STROKE		2	2	2	2	2
DISPLACEMENT CFM		39.8	39.8	59.6	59.6	59.6
OIL GRADE		150	150	150	150	150
OIL CHARGE PINTS		18	18	20	20	20
NET WEIGHT		480	546	690	730	760
RATED TONS	R-12	10.8	10.8	16.2	16.2	
	C-500	12.7	12.7		19	
	R-22		17.1			25.6
	R-502					
MOTOR SIZE HP		15	20	20	25	30
ELECTRICAL DATA						
200 -3- 60	LRA	150	214	214	279	360
	MAX RLA	32.9	46.5	46.5	54.3	70.8
	FUSETRON SIZE	50	70	70	80	100
230 -3- 60	LRA	150	214	214	279	360
	MAX RLA	32.9	46.5	46.5	54.3	70.8
	FUSETRON SIZE	50	70	70	80	100
460 -3- 60	LRA	75	107	107	140	180
	MAX RLA	17.2	24.3	24.3	29.6	35.4
	FUSETRON SIZE	25	35	35	45	50

RATING: Listed ratings are tons at 105° F. Sat. Cond.Temp., 40° F. Sat. Suction Temp.