

MODEL	MRA0500	MRF0500	MRB0500	MRG0500	MRH0760	MRG0750
NET OIL PRESSURE	20-60	20-60	20-60	20-60	20-60	20-60
CYLINDERS	2	2	2	2	2	2
BORE	2-1/2	2-1/2	2-5/8	2-7/16	2-9/16	2-7/16
STROKE	1-13/16	1-13/16	1-13/16	1-13/16	1-13/16	1-13/16
DISPLACEMENT CFH	1080	1080	1191	1020	1136	1020
OIL GRADE	150	150	150	150	150	150
OIL CHARGE OZ.	112	112	112	112	112	112
NET WEIGHT	266	269	269	269	281	291
RATED BTUH @ SST LISTED	R12 45°F		48600			
	R12 0°F	16000	15000	19100		
	R12 -20°F					
	R22 45°F				M	82.0 H
	R22 25°F			18100		
R502 0°F	27500					
MOTOR SIZE HP	5	5	5	5	7-1/2	7-1/2
ELECTRICAL DATA						
230 -1- 60	LRA	125.0	125.0	125.0	---	---
	RLA	27.5	23.5	27.5	---	---
	MCC	34.7	35.3	34.7	---	---
208-230 -3- 60	LRA	115.5	115.0	115.0	164.0	164.0
	RLA	22.0	21.0	21.2	30.3	32.8
	MCC	27.5	28.0	29.4	41.4	FRN-60
460 -3- 60	LRA	53.0	53.0	53.0	82.0	82.0
	RLA	8.6	8.7	12.1	13.5	15.9
	MCC	12.0	11.6	16.9	18.3	FRN-25

Conditions: 130° Condensing Temperature, 0° Subcooling, 65° RGT,